

UT54ACS244E

Features


- Three-state outputs drive bus lines or buffer memory address registers
- 0.6µm CRH CMOS Process
 - Latchup immune
- High speed
- Low power consumption
- Wide power supply operating range of 3.0V to 5.5V
- Available QML Q or V processes
- 20-lead flatpack
- UT54ACS244E - SMD - 5962-96570

Description

The UT54ACS244E is a performance and voltage enhanced version of the UT54ACS244 non-inverting octal buffers and line drivers which improve the performance and density of three-state memory address drivers, clock drivers, and bus-oriented receivers and transmitters.

The devices are characterized over full military temperature range of -55°C to +125°C.

Pinout




20-Lead Flatpack
Top View

Function Table

Inputs		Output
$\overline{1G}, \overline{2G}$	A	Y
L	L	L
L	H	H
H	X	Z

UT54ACS244E


Logic Symbol



Note:

1) Logic symbol in accordance with ANSI/IEEE standard 91-1984 and IEC Publication 617-12.

Logic Diagram



UT54ACS244E

Operational Environment ¹

Parameter	Limit	Units
Total Dose	1.0E6	rads(Si)
SEU Threshold ²	108	MeV-cm ² /mg
SEL Threshold	120	MeV-cm ² /mg
Neutron Fluence	1.0E14	n/cm ²

Notes:

- 1) Logic will not latchup during radiation exposure within the limits defined in the table.
- 2) Device storage elements are immune to SEU affects.

Absolute Maximum Ratings

Symbol	Parameter	Limit	Units
V _{DD}	Supply voltage	-0.3 to 7.0	V
V _{I/O}	Voltage any pin	-0.3 to V _{DD} +0.3	V
T _{STG}	Storage Temperature range	-65 to +150	°C
T _J	Maximum junction temperature	+175	°C
T _{LS}	Lead temperature (soldering 5 seconds)	+300	°C
Θ _{JC}	Thermal resistance junction to case	15	°C/W
I _I	DC input current	±10	mA
P _D ²	Maximum package power dissipation permitted @ T _c = +125°C	3.2	W

Notes:

- 1) Stresses outside the listed absolute maximum ratings may cause permanent damage to the device. This is a stress rating only, functional operation of the device at these or any other conditions beyond limits indicated in the operational sections is not recommended. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.
- 2) Per MIL-STD-883, method 1012.1, Section 3.4.1, $P_D = (T_{j(max)} - T_{c(max)}) / \Theta_{JC}$

Recommended Operating Conditions

Symbol	Parameter	Limit	Units
V _{DD}	Supply voltage	3.0 to 5.5	V
V _{IN}	Input voltage any pin	0 to V _{DD}	V
T _C	Temperature range	-55 to + 125	°C

UT54ACS244E

DC Electrical Characteristics for the UT54ACS244E ⁷

($V_{DD} = 3.0V$ to $5.5V$; $V_{SS} = 0V$ ⁶; $-55^{\circ}C < T_c < +125^{\circ}C$);

Symbol	Description	Condition	MIN	MAX	Unit
V_{IL}	Low-level input voltage ¹	$V_{DD} = 3.0V$ to $5.5V$		$0.3V_{DD}$	V
V_{IH}	High-level input voltage ¹	$V_{DD} = 3.0V$ to $5.5V$	$0.7V_{DD}$		V
I_{IN}	Input leakage current	$V_{IN} = V_{DD}$ or V_{SS}	-1	1	μA
V_{OL}	Low-level output voltage ³	$I_{OL} = 100\mu A$ $V_{DD} = 3.0V$ to $5.5V$		0.25	V
V_{OH}	High-level output voltage ³	$I_{OH} = -100\mu A$ $V_{DD} = 3.0V$ to $5.5V$	$V_{DD} - .025$		V
I_{OS1}	Short-circuit output current ^{2, 4}	$V_O = V_{DD}$ and V_{SS} V_{DD} from $4.5V$ to $5.5V$	-300	+300	mA
I_{OS2}	Short-circuit output current ^{2, 4}	$V_O = V_{DD}$ and V_{SS} V_{DD} from $3.0V$ to $3.6V$	-150	+150	mA
I_{OL1}	Low level output current ¹⁰	$V_{IN} = V_{DD}$ or V_{SS} $V_{OL} = 0.4V$ V_{DD} from $4.5V$ to $5.5V$	+12		mA
I_{OL2}	Low level output current ¹⁰	$V_{IN} = V_{DD}$ or V_{SS} $V_{OL} = 0.4V$ V_{DD} from $3.0V$ to $3.6V$	+8		mA
I_{OH1}	High level output current ¹⁰	$V_{IN} = V_{DD}$ or V_{SS} $V_{OH} = V_{DD} - 0.4V$ V_{DD} from $4.5V$ to $5.5V$	-12		mA
I_{OH2}	High level output current ¹⁰	$V_{IN} = V_{DD}$ or V_{SS} $V_{OH} = V_{DD} - 0.4V$ V_{DD} from $3.0V$ to $3.6V$	-8		mA
I_{OZ}	Three-state output leakage current	$V_O = V_{DD}$ and V_{SS}	-30	30	μA
P_{total1}	Power dissipation ^{2, 8, 9}	$C_L = 50pF$ V_{DD} from $4.5V$ to $5.5V$		1.5	mW/MHz
P_{total2}	Power dissipation ^{2, 8, 9}	$C_L = 50pF$ V_{DD} from $3.0V$ to $3.6V$		0.75	mW/MHz
I_{DDQ}	Quiescent Supply Current	$V_{IN} = V_{DD}$ or V_{SS} V_{DD} from $3.6V$ to $5.5V$		25	μA
C_{IN}	Input capacitance ⁵	$f = 1MHz$ $V_{DD} = 0V$		15	pF
C_{OUT}	Output capacitance ⁵	$f = 1MHz$ $V_{DD} = 0V$		15	pF

UT54ACS244E

Notes:

- 1) Functional tests are conducted in accordance with MIL-STD-883 with the following input test conditions: $V_{IH} = V_{IH(min)} + 20\%$, $- 0\%$; $V_{IL} = V_{IL(max)} + 0\%$, -50% , as specified herein, for TTL, CMOS, or Schmitt compatible inputs. Devices may be tested using any input voltage within the above specified range, but are guaranteed to $V_{IH(min)}$ and $V_{IL(max)}$.
- 2) Supplied as a design limit but not guaranteed or tested.
- 3) Per MIL-PRF-38535, for current density $\leq 5.0E5$ amps/cm², the maximum product of load capacitance (per output buffer) times frequency should not exceed 3,765pF/MHz.
- 4) Not more than one output may be shorted at a time for maximum duration of one second.
- 5) Capacitance measured for initial qualification and when design changes may affect the value. Capacitance is measured between the designated terminal and V_{SS} at frequency of 1MHz and a signal amplitude of 50mV rms maximum.
- 6) Maximum allowable relative shift equals 50mV.
- 7) For devices procured with a total ionizing dose tolerance guarantee, the post-irradiation performance is guaranteed at 25°C per MIL-STD-883 method 1019 condition A up to the maximum TID level procured.
- 8) Power does not include power contribution of any TTL output sink current.
- 9) Power dissipation specified per switching output.
- 10) Guaranteed by characterization, but not tested.

AC Electrical Characteristics for the UT54ACS244E ²

($V_{DD} = 3.0V$ to $5.5V$; $V_{SS} = 0V$ ¹, $-55^{\circ}C < T_c < +125^{\circ}C$);

Symbol	Parameter	Condition	V_{DD}	Minimum	Maximum	Unit
t_{PLH}	Input to Yn	CL = 50pF	4.5V to 5.5V	1	6.5	ns
			3.0V to 3.6V	1	9.5	
t_{PHL}	Input to Yn	CL = 50pF	4.5V to 5.5V	1	7.5	ns
			3.0V to 3.6V	1	10.5	
t_{PZL}	\bar{G} low to Yn active	CL = 50pF	4.5V to 5.5V	1	6	ns
			3.0V to 3.6V	1	8	
t_{PZH}	\bar{G} low to Yn active	CL = 50pF	4.5V to 5.5V	1	7	ns
			3.0V to 3.6V	1	9.5	
t_{PLZ}	\bar{G} high to Yn three-state	CL = 50pF	4.5V to 5.5V	1	6	ns
			3.0V to 3.6V	1	7.5	
t_{PHZ}	\bar{G} high to Yn three-state	CL = 50pF	4.5V to 5.5V	1	9.5	ns
			3.0V to 3.6V	1	11	

Notes:

- 1) Maximum allowable relative shift equals 50mV.
- 2) For devices procured with a total ionizing dose tolerance guarantee, the post-irradiation performance is guaranteed at 25°C per MIL-STD-883 method 1019 condition A up to the maximum TID level procured.

UT54ACS244E

Packaging





Figure 1. 20-lead Flatpack

Notes:

- 1) All exposed metallized areas are gold plated over electroplated nickel per MIL-PRF-38535.
- 2) The lid is electrically connected to V_{SS} .
- 3) Lead finishes are in accordance with MIL-PRF-38535.
- 4) Dimension symbol is in accordance with MIL-PRF-38533.
- 5) Lead position and colanarity are not measured.

UT54ACS244E

Ordering Information: UT54ACS244E: SMD



Notes:

- 1) Lead finish (A,C, or X) must be specified.
- 2) If an "X" is specified when ordering, part marking will match the lead finish and will be either "A" (solder) or "C" (gold).
- 3) Total dose radiation must be specified when ordering. QML Q and QML V not available without radiation hardening. For prototype inquiries, contact factory.
- 4) Device type 02 is only offered with a TID tolerance guarantee of 3E5 rads(Si) or 1E6 rads(Si) and is tested in accordance with MIL-STD-883 Test Method 1019 Condition A and section 3.11.2. Device type 03 is only offered with a TID tolerance guarantee of 1E5 rads(Si), 3E5 rads(Si), and 5E5 rads(Si), and is tested in accordance with MIL-STD-883 Test Method 1019 Condition A.

Datasheet Revision History

Revision Date	Description of Change
March 2015 Version 1.0.0	Initial Release of Datasheet

UT54ACS244E

Datasheet Definitions

	DEFINITION
Advanced Datasheet	CAES reserves the right to make changes to any products and services described herein at any time without notice. The product is still in the development stage and the datasheet is subject to change . Specifications can be TBD and the part package and pinout are not final .
Preliminary Datasheet	CAES reserves the right to make changes to any products and services described herein at any time without notice. The product is in the characterization stage and prototypes are available.
Datasheet	Product is in production and any changes to the product and services described herein will follow a formal customer notification process for form, fit or function changes.

The following United States (U.S.) Department of Commerce statement shall be applicable if these commodities, technology, or software are exported from the U.S.: These commodities, technology, or software were exported from the United States in accordance with the Export Administration Regulations. Diversion contrary to U.S. law is prohibited.

Cobham Colorado Springs Inc. d/b/a Cobham Advanced Electronic Solutions (CAES) reserves the right to make changes to any products and services described herein at any time without notice. Consult an authorized sales representative to verify that the information in this data sheet is current before using this product. The company does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing; nor does the purchase, lease, or use of a product or service convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of the company or of third parties.